

Playlist+

COLOURED-BODY PORCELAIN

Panaria
ceramica

MADE IN
USA 



AMBIENT WHITE
PLY10



CLASSICAL BEIGE
PLY20



GRUNGE GREIGE
PLY30




GOTHIC GREY
PLY40




FOLK GREEN
PLY60




**NEW-AGE
TERRACOTTA**
PLY80



**RHYTHM AND
BLUES**
PLY110




SYNTH BLACK
PLY120



12"x24" - 30x60 cm
SOFT


DECOS




MOSAIC 36 PCS
PLY40M122

12"x12" - 30x30 cm
SOFT
± 8 mm

TRIM PIECES



BULLNOSE
4"x24" - 9.5x60 cm
SOFT
± 8 mm



COVE BASE
6"x12" - 15x30 cm
SOFT
± 8 mm



COVE BASE CORNER
6"x1" - 15x2.5 cm
SOFT
± 8 mm

(Cove Base & Cove Base Corner are special order only)

COLOURED-BODY PORCELAIN

TECHNICAL FEATURES

COLOURED-BODY PORCELAIN according to ANSI A137.1 (Glazed Porcelain Tiles - P1 Class)

TECHNICAL FEATURES	TEST METHOD	REQUIRED VALUES	AVERAGE VALUES
WATER ABSORPTION	ASTM C373	≤ 0.5%	CONFORMS
BREAKING STRENGTH	ASTM C648	≥ 250 lbf	≥350 lbf
SURFACE ABRASION RESISTANCE	ASTM C1027	As indicated by manufacturer	PEI 4
SLIP RESISTANCE	ANSI A326.3	-	IW+ 8 mm Soft
SHADE VARIATION	ANSI A137.1	As indicated by manufacturer	V2

PACKINGS AND WEIGHTS

SIZES	SF / CTN	PIECES / CTN	CTN / PALLET	SF / PALLET	LBS / CTN	LBS / PALLET
12"x24" Soft	18	9	32	576.00	59.10	1,941
MOSAIC 36 PCS 12"x12" Soft	4.84	5	90	436.05	15.10	1,409
BULLNOSE 4"x24" Soft	9.82	16	60	589.20	33.80	2,078
COVE BASE 6"x12" Soft	3.93	8	108	424.44	14.96	1,666
COVE BASE CORNER 6"x1" Soft	0.17	4	600	102.00	0.80	530

INTENDED USE

KEY



RESIDENTIAL

Kitchens, bathrooms, living rooms and other residential environments.



LIGHT COMMERCIAL

Offices, offices open to the general public, waiting rooms, shops, public bathrooms, common apartment block areas, restaurant dining rooms, car showrooms, bars, cinemas, surgeries/clinics, hotel rooms and bathrooms.



INTENSIVE COMMERCIAL

Common areas of shopping centres, hotel foyers, canteens, fast food restaurants, dance clubs, hospitals, schools, museums, places of worship, airports, stations.



OUTDOOR

Mainly for external areas that require flooring with anti-slip characteristics.